



NOTE:

- MATERIAL  
HOUSING: GLASS-REINFORCED THERMOPLASTIC UL 94V-0.  
CONTACT: COPPER ALLOY.  
PLATING: TIN PLATED OVER NICKEL
- ELECTRICAL  
CURRENT RATING: 3.0AMP.  
DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC MIN.  
INSULATION RESISTANCE: 1000MΩ MIN.  
CONTACT RESISTANCE: 30mΩ MAX.
- ENVIRONMENTAL  
TEMPERATURE RANGE: -25°C TO 85°C.

■ DIMENSION TABLE

Circuits	Dimension			Circuits	Dimension		
	A	B	C		A	B	C
2	10.54	8.43	2.54	20	56.26	54.15	48.26
3	13.08	10.97	5.08				
4	15.62	13.51	7.62				
5	18.16	16.05	10.16				
6	20.70	18.59	12.70				
7	23.24	21.13	15.24				
8	25.78	23.67	17.78				
9	28.32	26.21	20.32				
10	30.86	28.75	22.86				
11	33.40	31.29	25.40				
12	35.94	33.83	27.94				
13	38.48	36.37	30.48				
14	41.02	38.91	33.02				
15	43.56	41.45	35.56				
16	46.10	43.99	38.10				
17	48.64	46.53	40.64				
18	51.18	49.07	43.18				
19	53.72	51.61	45.72				

<p>RoHS Compliant</p>		<p><b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>											
<p>APPD. 核准</p>		<p>TOLERANCE</p> <table border="1"> <tr> <th>LINEAR</th> <th>ANGLES</th> </tr> <tr> <td>X±0.40</td> <td>X°±</td> </tr> <tr> <td>X±0.30</td> <td>X°±</td> </tr> <tr> <td>.XX±0.20</td> <td>.XX°±</td> </tr> <tr> <td>.XXX±0.10</td> <td>.XXX°±</td> </tr> </table>	LINEAR	ANGLES	X±0.40	X°±	X±0.30	X°±	.XX±0.20	.XX°±	.XXX±0.10	.XXX°±	<p>PART NAME 品名</p> <p>FFC/FPC NON-ZIF 2.54mm DUAL CONTACT XXP 180° TIN PLATING BLACK COLOR ROHS</p>
LINEAR	ANGLES												
X±0.40	X°±												
X±0.30	X°±												
.XX±0.20	.XX°±												
.XXX±0.10	.XXX°±												
<p>DWG. 製圖 HELEN</p>	<p>SCALE 比例 參考</p>	<p>UNIT 單位 MM</p>	<p>PART NO. 料號 C3900-XXDTTB00R</p>										
<p>DATE 制表日 2022/8/16</p>	<p>PAGE 張數 1 OF 1</p>	<p>SIZE 紙張尺寸 A4</p>	<p>REV. 版本 B</p>										