



CKT	A	B	C
3	6.0	4.1	2.0
4	7.0	5.1	3.0
5	8.0	6.1	4.0
6	9.0	7.1	5.0
7	10.0	8.1	6.0
8	11.0	9.1	7.0
9	12.0	10.1	8.0
10	13.0	11.1	9.0
11	14.0	12.1	10.0
12	15.0	13.1	11.0
13	16.0	14.1	12.0
14	17.0	15.1	13.0
15	18.0	16.1	14.0
16	19.0	17.1	15.0
17	20.0	18.1	16.0
18	21.0	19.1	17.0
19	22.0	20.1	18.0
20	23.0	21.1	19.0
21	24.0	22.1	20.0
22	25.0	23.1	21.0
23	26.0	24.1	22.0
24	27.0	25.1	23.0
25	28.0	26.1	24.0
26	29.0	27.1	25.0
27	30.0	28.1	26.0
28	31.0	29.1	27.0
29	32.0	30.1	28.0
30	33.0	31.1	29.0
31	34.0	32.1	30.0
32	35.0	33.1	31.0

Item	Requirement	Test Condition
Rated Voltage	200V(ac/dc)	
Rated Current	1Amp(ac/dc)	
Contact Resistance	20mΩ	Mate connectors measure by dry circuit 20mV max, 10mA.
Insulation Resistance	500MΩ	Mate connectors, apply 500V dc between adjacent terminal or ground.
Dielectric Strength	No Breakdown	Mate connectors, apply 500V ac for 1 minute between adjacent terminal or ground.

NOTE:  
 1. MATERIAL:  
 HOUSING: LCP  
 TERMINAL: PHOSPHOR BRONZE  
**Ambient Temperature Range:** -40 degree to +105 degree

RoHS Compliant		<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准: BETTY	SCALE 比例: 参考	TOLERANCE: 0.0 ±0.25, 0.00 ±0.20, 0.000 ±0.10	PART NAME 品名: FPC/FFC NON-ZIF 1.0mm XXP DIP 180° REVERSE LAYOUT TIN PLATING TUBE PACKING BEIGE COLOR ROHS
DWG. 製圖: KAREN	UNIT 單位: MM	SIZE 紙張尺寸: A4	PART NO. 料號: C3920-XXETTC00R
DATE 制表日: 2012/08/13	PAGE 張數: 1 OF 1	REV. 版本: C	