



Tolerance	
0 ~ 3	±0.13
>3 ~ 18	±0.16
>18 ~ 50	±0.31
>50	±0.55
Ang.	±1°

APPLICABLE PCB LAYOUT

12	40.50	33.28	27.94	25.40
11	37.96	30.74	25.40	17.78
10	35.42	28.20	22.86	15.24
9	32.88	25.66	20.32	12.70
8	30.34	23.12	17.78	10.16
PIN	A	B	C	D
	SIZE			

NOTE:

- Retention force: The retention force of the insert spring in the plastic part is $\geq 10N$.
- Contact resistance: $\leq 0.03\Omega$.
- Insulation resistance: $\geq 1000M\Omega$.
- Withstand voltage: 1000V (50 Hz, effective value; 1 min).

3	ACTUATOR	PBT	1	UL94V-0 Blue Color
2	HOUSING	PBT	1	UL94V-0 Blue Color
1	TERMINAL	C5191	N	Tin-plated
NO.	NAME	MATERIAL	Q'TY	REMARK

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		PART NAME 品名	
DWG. 製圖	Betty	2.54mm ZIF FFC/FPC XXPIN TOP ENTRY TYPE (DIP STRAIGHT) TIN PLATING BLUE COLOR WITH KINK PIN ROHS	
DATE 制表日	2020/09/03	PAGE 張數	1 OF 1
		REV. 版次	A
		PART NO. 料號	
		C3951-XXTTLY00R	