



NOTE:

- MATERIAL**
 HOUSING: GLASS-REINFORCED THERMOPLASTIC UL 94V-0.
 CONTACT: COPPER ALLOY.
 PLATING: TIN PLATED OVER NICKEL. (Ni:30U" MIN, Tin:80U" MIN.)
- ELECTRICAL**
 CURRENT RATING: 0.5 AMP.
 DIELECTRIC WITHSTANDING VOLTAGE:250V AC MIN.
 INSULATION RESISTANCE: 100MΩ MIN.
 CONTACT RESISTANCE: 30mΩ MAX.
- ENVIRONMENTAL**
 TEMPERATURE RANGE: -25°C TO +85°C.

■ DIMENSION TABLE

Circuits	Dimension			Circuits	Dimension			Circuits	Dimension		
	A	B	C		A	B	C		A	B	C
4	1.50	2.60	4.90	23	11.00	12.10	14.40	42	20.50	21.60	23.90
5	2.00	3.10	5.40	24	11.50	12.60	14.90	43	21.00	22.10	24.40
6	2.50	3.60	5.90	25	12.00	13.10	15.40	44	21.50	22.60	24.90
7	3.00	4.10	6.40	26	12.50	13.60	15.90	45	22.00	23.10	25.40
8	3.50	4.60	6.90	27	13.00	14.10	16.40	46	22.50	23.60	25.90
9	4.00	5.10	7.40	28	13.50	14.60	16.90	47	23.00	24.10	26.40
10	4.50	5.60	7.90	29	14.00	15.10	17.40	48	23.50	24.60	26.90
11	5.00	6.10	8.40	30	14.50	15.60	17.90	49	24.00	25.10	27.40
12	5.50	6.60	8.90	31	15.00	16.10	18.40	50	24.50	25.60	27.90
13	6.00	7.10	9.40	32	15.50	16.60	18.90	51	25.00	26.10	28.40
14	6.50	7.60	9.90	33	16.00	17.10	19.40	52	25.50	26.60	28.90
15	7.00	8.10	10.40	34	16.50	17.60	19.90	53	26.00	27.10	29.40
16	7.50	8.60	10.90	35	17.00	18.10	20.40	54	26.50	27.60	29.90
17	8.00	9.10	11.40	36	17.50	18.60	20.90	55	27.00	28.10	30.40
18	8.50	9.60	11.90	37	18.00	19.10	21.40	56	27.50	28.60	30.90
19	9.00	10.10	12.40	38	18.50	19.60	21.90	57	28.00	29.10	31.40
20	9.50	10.60	12.90	39	19.00	20.10	22.40	58	28.50	29.60	31.90
21	10.00	11.10	13.40	40	19.50	20.60	22.90	59	29.00	30.10	32.40
22	10.50	11.60	13.90	41	20.00	21.10	23.40	60	29.50	30.60	32.90

RoHS Compliant **HSM** 玄茂科技股份有限公司 **HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准	SCALE 比例 參考	TOLERANCE X ±0.30 X.X ±0.20 X.XX ±0.15 X.XXX ±0.08	PART NAME 品名 0.5mm NON-ZIF FFC/FPC CONNECTOR SMT VERTICAL TYPE XXPIN TIN PLATING REEL PACKING IVORY COLOR ROHS
DWG. 製圖		UNIT 單位 M M	
DATE 制表日	PAGE 張數 1 OF 1	REV. 版次 A	
2023/09/15			

