


ϕ Dim	No. of Pin
ϕ 3.0mm	2PIN
ϕ 4.0mm	03~40PIN

Specifications
 Current Rating: 1Amp
 Insulation Resistance: 1000M Ω Min.
 Dielectric Withstanding: 300V AC
 Contact Resistance: 20m Ω Max.
 Operating Temperature: -40°C to +105°C

Materials
 Contact Material: Phosphor Bronze
 Insulation Material: High Temperature Thermoplastic, UL 94V-0 LCP or the equivalent material

Recommended P.C. Board Layout
 (Tolerance: ± 0.05)



RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	GENERAL TOLERANCE X' $\pm 5.0'$ X ± 0.30 X" $\pm 3.0'$ X ± 0.25 XXX' $\pm 2.0'$ XXX ± 0.15 XXXX' $\pm 1.0'$ XXXX ± 0.10
DWG. 製圖 Betty	UNIT 單位 MM	SIZE. 紙張尺寸 A4
DATE 製表日 2017/06/20	PAGE 張數 1 OF 1	REV. 版次 C
PART NAME 品名 1.27mm FEMALE HEADER SINGLE ROW H:1.95mm SMT A TYPE 1XXXP WITHOUT LOCATING PEG MATERIAL: LCP ROHS		PART NO. 料號 C4832-XXADXHNXR