



Current Rating: 1 Amps
 Insulator Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms max
 Dielectric Withstanding: 500 V AC
 Operating Temperature: - 40° ~ +105° C
 Max Processing Temp: 230° C for 60 seconds
 Max Processing Temp: 260° C for 10 seconds
 Contact Material: Phosphor Bronze
 Insulator Material: High Temperature (Nylon-9T)
 Plastic, UL 94V-0

Standard: Gold Flash all over

Recommended P.C. Board
SMD Layout

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	Betty	SCALE 比例	1.27x1.27mm FEMALE HEADER DUAL ROWS 2XXXP RIGHT ANGLE TYPE H=4.4mm GOLD FLASH PLATING WITHOUT LOCATING PEG TUBE PACKING BLACK COLOR MATERIAL: NYLON 9T DIP LENGTH=2.4mm ROHS
DATE 制表日	2015/06/03	UNIT 單位	PART NO.
		PAGE 張數	料號
		1 OF 1	C4833-XXBRGHNTB
		REV. 版次	
		A	