



**MATERIAL**  
 HOUSING : THERMOPLASTIC UL94V-0  
 CONTACT : COPPER ALLOYS

**SPECIFICATION**  
 CURRENT: 1A  
 OPERATING TEMPERATURE: -55°C TO +105°C  
 CONTACT RESISTANCE : 20 MILLIOHMS MAX  
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN  
 DIELECTRIC STRENGTH : 1000 VAC MIN

**RoHS  
 Compliant**

**HSM 玄茂科技股份有限公司  
 HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准 HELEN  
 DWG. 製圖 ABBY  
 DATE 制表日 2012/08/16

SCALE 比例 參考  
 UNIT 單位 MM  
 PAGE 張數 1 OF 1  
 TOLERANCE 容許公差  
 .0 ± 0.38  
 .00 ± 0.25  
 ANG. ± 5°  
 SIZE 紙張尺寸 A4  
 REV. 版本 B

**PART NAME 品名**  
 2.0mm PIN HEADER DUAL ROW  
 2XXXP S.M.T. TYPE H=1.5mm  
 (C=3.8mm D=6.5mm E=2.2mm) ROHS  
**PART NO. 料號**  
 C6215-XXBDXATXR