



Specifications
 Current Rating: 2Amp
 Insulation Resistance: 1000M Ω Min.
 Dielectric Withstanding Voltage: 500VAC
 Contact Resistance: 20m Ω Max.
 Operating Temperature: -40°C to +105°C
 Materials
 Contact Material: Phosphor Bronze
 Insulator Material: High Temperature Thermoplastic, UL 94V-0 Nylon 6T or the equivalent material

RECOMMENDED P.C.B LAYOUT
 FOR BOTTOM ENTRY
 (Tolerance: ± 0.05)

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY		TOLERANCE X: $\pm 5.0'$ X: ± 0.30 .X: $\pm 3.0'$ X: ± 0.25 .XX: $\pm 2.0'$ X: ± 0.15 .XXX: $\pm 1.0'$ X: ± 0.10	PART NAME 品名 2.0mm FEMALE HEADER SINGLE ROW SMT B TYPE 1*XXP W/O LOCATING PEG INSULATOR HEIGHT: 4.3mm ROHS
DWG. 製圖 KAREN	SCALE 比例 參考	UNIT 單位 M M	PART NO. 料號 C6802-XXCDXCNXR
DATE 制表日 2014/10/17	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A 4	