



**Specifications rating :**

- 100V AC 1A MAX**
- contact resistance :**
- pins-30mΩ MAX; shell-50mΩ MAX**
- insulation resistance :**
- MIN 100 MEGΩ @500V DC**
- voltage withstand :**
- 250V AC R.M.S. for 1 minute**

5	8P 270 Housing	ABS		1
4	Terminals	Brass	Silver Ptd.	8
3	Shield Cover B	Steel	Nickel Ptd.	1
2	Shield Cover A	Steel	Nickel Ptd.	1
1	Shell Cover 6.0	EVA+LLDPE		1
No.	Description	Material	Traet	Q'ty

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
		PART NAME 品名 DIN (ASSEMBLY TYPE) 8P FEMALE 270° NICKEL PLATING ROHS	
APPD. 核准 Hedy		TOLERANCE 容許公差 .X +/-0.25 .XX +/-0.10	PART NO. 料號 C8000-08FBNB00R
DWG. 製圖 Hedy	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1	SIZE. 紙張尺寸 A 4 REV. 版次 A	
DATE 制表日 2013/06/18			