



PCB LAYOUT
(TOP VIEW)

SPECIFICATIONS:

1. CONTACT RESISTANCE : 20m OHM MAX.
2. INSULATION RESISTANCE : 300M OHM MIN. AT DC 500V.
3. VOLTAGE WITHSTANDING : AC 1000V FOR ONE MINUTE.
4. INSERTION FORCE : 4.0KG MAX.
5. WITHDRAWAL FORCE : 1 - 3.5KG.

5.	RIVET	1	AL	NICKEL PLATED	
4.	CONTACT TERMINAL	8	BRASS 0.7t	TIN	
3.	EARTH TERMINAL	1	PBSR-H 0.25t	TIN	
2.	INSULATOR	1	P.B.T.		UL94V-0
1.	SOCKET CASE	1	SPCC-SD 0.4t	NICKEL PLATED	

P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS
-----	-----------	------	----------	---------	---------

RoHS Compliant
HSM
玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准		TOLERANCE 容許公差	PART NAME 品名 DIN SOCKET METAL COVER TYPE P.C.B TYPE XXP TIN PLATING BLACK COLOR ROHS
DWG. 製圖		0.0 ± 0.3 0.00 ± ANG ±	
DATE 制表日	UNIT 單位	SIZE 線規尺寸	PART NO. 料號 C8015-(04,06,07,08)BTB000R
2014/10/17	M M	A 4	
	PAGE 張數	REV. 版本	
	1 OF 1	A	

ARRANGEMENT OF CONTACTS	MODEL NO.	4P	6P	7P	8P
		4P	6P	7P	8P
HOLE LAYOUT					