



Specifications  
rating :  
100V AC 1A MAX  
contact resistance :  
pins-30mΩ MAX; shell-50mΩ MAX  
insulation resistance :  
MIN 100 MEGΩ @500V DC  
voltage withstand :  
250V AC R.M.S. for 1 minute

section A-A

8	Terminals	Brass	Silver Ptd.	8
7	Housing	PA66		1
6	Strain Boot	PVC		1
5	Set Screw	Steel	Nickel Ptd.	1
4	Spring	Steel	Nickel Ptd.	1
3	"T" Cable Holder	Steel	Nickel Ptd.	1
2	Screw Cap	Brass	Nickel Ptd.	1
1	Shell Cover	Brass	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 DATE 制表日 2018/7/18	 SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE 容許公差 0 ± 0.35 .00 ± 0.25 ANG. ± 3° SIZE 線張尺寸 A 4 REV. 版本 A	PART NAME 品名 DIN CABLE JACK SCREW LOCK 5P FEMALE 180 DEGREES NICKEL SHELL SILVER PLATING BALCK INSULATOR(NYLON 66) ROHS PART NO. 料號 C8020-08FVBC00L