



UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

T:1.6 Dimensions of PC board holes  
Tolerance : ±0.05(Printed-Top view)

5	COAT	1	SPCC	t=0.4	Cu/Sn	PLATED
4	GROUND CONTACT	1	C2680	t=0.4	Cu/Sn	PLATED
3	TERMINAL	4	C2680	t=0.3	Ag	PLATED
2	COVER	1	PBT 4815		UL-94V0	(BLACK)
1	HOUSING	1	PBT 4815		UL-94V0	(BLACK)
LTR	PART NAME	QTY	MATERIAL			REMARK

<p>RoHS Compliant</p>	<p><b>HSM</b> 玄茂科技股份有限公司</p> <p><b>HSUAN MAO TECHNOLOGY CO., LTD.</b></p>	
	<p>APPD. 核准</p> <p>DWG. 製圖</p> <p>DATE 制表日</p> <p>2014/08/13</p>	<p>SCALE 比例</p> <p>UNIT 單位</p> <p>PAGE 張數</p> <p>1 OF 1</p>
<p>PART NAME 品名</p> <p>MINI DIN JACK 4P WITH FULLY SHIELDED WITH BOARDLOCK FOOT MATERIAL : PBT BLACK INSULATOR ROHS</p>		
<p>PART NO. 料號</p> <p>C8023-04FAFVB0R</p>		