



SPECIFICATIONS

Contact resistance	30mΩ Max.
Dielectric strength	250V AC/1 Minute
Insulation resistance	50MΩ Min. at 250V DC
Rating	100V AC 1A Max.; 12V DC 2A Max.
Insertion force	4.5Kg Max.
Withdrawal force	0.9Kg ~ 3Kg

3	HEX. NUT	1	BRASS	NICKEL	30-50u"
3	EARTH TERMINAL	1	BSR-H (0.3t) [C2680R]	NICKEL	30-50u"
2	CONTACT TERMINAL	8	BSR-H (0.2t) [C1519R-H]	SILVER PLATED	30-50u"
1	PLASTIC BODY	1	PBT [D202G15]		UL94HB
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准
DWG. 製圖
DATE 制表日
2016/11/18

SCALE 比例 參考
UNIT 單位 M M
PAGE 張數 1 OF 1

TOLERANCE 容許公差
.0 ± 0.30
.00 ± 0.20
ANG. ± 3°
SIZE. 紙張尺寸 A 4
REV. 版次 A

PART NAME 品名
MINI DIN JACK SQUARE HOLE TYPE
XXPIN VERTICAL TYPE WITH NUT
WITH LOCK PIN: SILVER PLATED ROHS

PART NO.
料號 C8096-XXPVBYY0R

A
B
C
D
E
F
G
H

A
B
C
D
E
F
G
H

1 2 3 4 5 6 7 8