



NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	PBT G.F.	BLACK	1	
2	CONTACT	PHOS. BRONZE T:0.2	GOLD-TIN PLATED	6	Gold:1~3u"; NI:40~60u"; TIN:120u" (100% pure Tin of lead free plating)
3	SHIELD	BRASS T:0.3	TIN PLATED	1	TIN:120~200u"
4	BOTTOM COVER	PBT G.F.	BLACK	1	
5	SPRING SHIELD	STAINLESS T:0.2		1	

Specification:  
 Rated Voltage and Current: DC 12A,2A max; AC 100V,1A max  
 Operating Temp: -25°C~+70°C  
 Insulation Resistance:100MΩ min at 500VDC  
 Dielectric Withstanding Voltage: 250V AC For 1min  
 Contact Resistance:30mΩ max  
 Operating Temp:-25°C~+70°C

RoHS Compliant		<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 Angel	SCALE 比例 参考	TOLERANCE 容許公差 .0 ±0.3 .00 ± ANG. ±	PART NAME 品名 MINI DIN JACK 6P FULLY SHIELDED+GROUNDING STRIP KINK TYPE SELECTIVE GOLD PLATING BLACK INSULATOR ROHS LOW-LEAD
DWG. 製圖 Yumi	UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. 料號 C8102-06GKSB00R
DATE 制表日 2009/12/04	PAGE 張數 1 OF 1	REV. 版次 A	