



NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	C.R.S T:0.3	TIN-PLATED	1
2	TERMINAL	BRASS T:0.25	TIN-PLATED	1
3	BRACKET	C.R.S T:0.4	TIN-PLATED	1
4	INSULATOR	PBT G.F.	WHITE	1
5	RING	PBT G.F.	RED	1

Specification:

Contact Resistance: 30m Ohm. Max. At AC 100mA Max. 1KHz.

Insulation Resistance: 100M Ohm Min. At 500V DC.

Rated Voltage And Current: DC 12V, 2A Max ; AC 100V, 1A Max.

Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.

Durability (Life Test): 4000 Cycles.

Insertion Force: 0.3~3.0 Kg.

Extraction Force: 0.3~3.0 Kg.

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 参考	TOLERANCE 容許公差 X ±0.38 XX ±0.25 XXX ±0.13 XXX ±0.05	PART NAME 品名 RCA JACK 2 CONTACTS RED INSULATOR ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號 C8106-02TR0000R
DATE 制表日 2012/10/25	PAGE 張數 1 OF 1	REV. 版次 A	