



Specification:

Contact Resistance: 30m Ohm. Max. At AC 100mA Max. 1KHz.
 Insulation Resistance: 100M Ohm Min. At 500V DC.
 Rated Voltage And Current: DC 12V, 2A Max ; AC 100V, 1A Max.
 Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute
 Durability (Life Test): 4000 Cycles
 Insertion Force: 0.3~3.0 Kg.
 Extraction Force: 0.3~3.0Kg.

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	BRASS T:0.40	NICKEL PLATED	2
2	JACK HOUSING	PBT G.F.	RED, WHITE	2
3	ASSEM. HOUSING	ABS	BLACK	1
4	CONTACT TERM.	BRASS T:0.50	TIN PLATED	2

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 参考	TOLERANCE X ± 0.38 X ± 0.25 XX ± 0.13 XXX ± 0.05	PART NAME 品名 RCA JACK 2 PORT (RED/WHITE) HORIZONTAL TYPE RIGHT ANGLE O.D.=8.3mm 4P METAL FOOT, 2P PLASTIC FOOT ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE 紙張尺寸 A4	PART NO. 料號 C8108-02HT0000R
DATE 制表日 2011/09/21	PAGE 張數 1 OF 1	REV. 版本 A	