



6.	Cover	PA9T	1	Black Color
5.	Housing	PA9T	1	Black Color
4.	Pin(2.0φ)	Copper	1	Nickel Plated
3.	Break Terminal	0.4T Brass	1	Silver Plated
2.	Sleeve Spring	0.25T Phosphor Bronze	1	Silver Plated
1.	Pin Terminal	0.4T Brass	1	Silver Plated
<b>NO.</b>	<b>Description</b>	<b>Material</b>	<b>Q'TY</b>	<b>Finish</b>

**SPECIFICATIONS:**  
**Contact Resistance** : 30mΩ max  
**Current Rating** : Max 5.0A , 24V DC  
**Insulation Resistance** : 100MΩ min. at DC 500V  
**Dielectric Withstand Voltage** : AC 500V for one minute  
**Remark:** ▲: The Most Important Dimension

APPD. 核准 DWG. 製圖 DATE 制表日 2015/03/09	 SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3° SIZE. 紙張尺寸 A 4 REV. 版次 A	<b>RoHS Compliant</b>	<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>
			PART NAME 品名 DC POWER JACK PIN:2.0mm NORMAL CLOSE FLAT TYPE SILVER PLATED BLACK INSULATOR WITH LOCATING PEG ROHS	PART NO. 料號 C8125-CCVBY000R