



SCHEMATIC	
	Model No: C

NO.	Description	Material	Q'TY	Finish
8.	Insulator B	Red Vulcanited Fibre	1	Red Color
7.	Insulator A	Red Vulcanited Fibre	1	Red Color
6.	Pin(2.0φ)	Copper	1	Nickel Plated
5.	Bushing	Brass	1	Nickel Plated
4.	Pin Terminal	0.3T Brass	1	Silver Plated
3.	Break Terminal	0.3T Brass	1	Silver Plated
2.	Sleeve Spring	0.4T Phosphor Bronze	1	Silver Plated
1.	Housing	PBT	1	Black Color

Pin Hole Layout  
(Jack Bottom View)

**SPECIFICATIONS:**  
**Contact Resistance** : 30mΩ max  
**Insulation Resistance** : 100MΩ min. at DC 500V  
**Dielectric Withstand Voltage** : AC 500V for one minute  
**Remark:** ▲ : The Most Important Dimension

RoHS Compliant	<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 Ivy		TOLERANCE 容許公差 .0 ±0.3 .00 ± ANG. ±
DWG. 製圖 Yumi	SCALE 比例 參考	SIZE. 紙張尺寸 A 4
DATE 制表日 2011/04/06	UNIT 單位 M M	REV. 版次 A
	PAGE 張數 1 OF 1	PART NAME 品名 DC POWER JACK RIGHT ANGLE TYPE PINφ2.0mm NORMAL CLOSE TYPE FLAT TYPE WITH THREADSILVER PLATING BLACK INSULATOR ROHS
		PART NO. 料號 C8141-CCFYVBN0R