



**Pin Hole Layout**  
(Jack Bottom View)

**SPECIFICATIONS:**  
 Contact Resistance : 30m $\Omega$  max  
 Current Rating : Max 5.0A, 24VDC  
 Insulation Resistance : 100M $\Omega$  min. at DC 500V  
 Dielectric Withstand Voltage : AC 500V for one minute

5.	Cover	PA9T	1	Black Color
4.	Housing	PA9T	1	Black Color
3.	Pin	0.2T Bronze	1	Tin Plated
2.	Spring Terminal	0.2T Phosphor Bronze	1	Tin Plated
1.	Earth Terminal(Barrel)	0.3T Phosphor Bronze	1	Tin Plated
NO.	Description	Material	Q'TY	Finish

RoHS  
Compliant

**HSM 玄茂科技股份有限公司**  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准  
 DWG. 製圖  
 DATE 制表日  
 2015/02/04

SCALE 比例 參考  
 UNIT 單位 M M  
 PAGE 張數 1 OF 1

TOLERANCE 容許公差  
 .0 ± 0.30  
 .00 ± 0.20  
 ANG. ± 3°  
 SIZE. 紙張尺寸 A 4  
 REV. 版次 A

PART NAME 品名  
 DC POWER JACK PIN :1.0mm FLAT TYPE  
 TIN PLATED BLACK INSULATOR ROHS

PART NO.  
 料號 C8147-ETB00000R