



Specification:  
 Current Rating: 3A  
 Voltage Rating: 170V max  
 Operating Temp: -30°C~+60°C  
 Insulation Resistance:  $\leq 100M\Omega$   
 Dielectric Withstanding Voltage: 2000V rms  
 Contact Resistance:  $\leq 20m\Omega$

7	CRIMPING PATCH	BRASS
6	SOLDERING PATCH	BRASS
5	DIELECTRIC	POM
4	BODY	Zn
3	PLASTIC HANDLE	PE
2	DIELECTRIC	POM
1	FRONT POINT	Zn
ITEM	DESIGNATION	MATERIAL

RoHS Compliant		<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 <b>HELEN</b>	SCALE 比例 参考	TOLERANCE 0 - 10 ±0.05 10 - 99 ±0.5 100 - 999 ±10.0 1000 - 9999 ±100.00 10000 - 99999 ±1000.00	PART NAME 品名 6.3mm PHONE PLUG STEREO PLASTIC HEXAGON TYPE(PE) NICKEL PLATING BLACK COLOR ROHS
DWG. 製圖 <b>ABBY</b>	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 <b>C8150-03MCENB0R</b>
DATE 制表日 2012/08/14	PAGE 張數 1 OF 1	REV. 版次 A	