

	1	2	3	4	5	6	7	8
A					<b>O/FORCE</b> <input type="checkbox"/> 180gf <input type="checkbox"/> 250gf <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>		<b>General specifications</b> Circuit : PUSH ON Rating : D.C. 12V 50mA Contact R.[max] : D.C. 5V 1A 100mΩ Insulation R.[min] : D.C. 100V 100MΩ Withstand VOL. : A.C. 250V 1minute Operating force : NA Life cycle[max] : 500,000 CYCLES	
B					<b>SCHEMATIC</b> 		<b>LAYOUT</b> 	
C							<b>MODEL NO.</b>	
D					<b>MODEL NO.</b>		<b>KNOB(L)</b>	
E					<input type="checkbox"/> 4.3 mm		<input type="checkbox"/> 5 mm	
F					<input type="checkbox"/>		<input type="checkbox"/>	
G	<b>RoHS Compliant</b>				<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>			
H					APPD. 核准 DWG. 製圖 Hedy DATE 制表日 2013/06/21		TOLERANCE UP TO 10 ±0.3 ABOVE 10 TO 100 ±0.5 ABOVE 100 ±0.8 ANGULAR DIMENSIONS ±5°	
	1	2	3	4	5	6	7	8