



P.C.B LAYOUT

RATING: DC12V 50mA  
 WITHSTAND VOLTAGE: AC250V(50Hz)/min  
 CONTACT RESISTANCE:  $\leq 30m\Omega$   
 INSULATION RESISTANCE:  $\geq 100M\Omega$   
 TRAVEL TO CLOSURE:  $0.25 \pm 0.1mm$   
 OPERATION FORCE:  $180gf \pm 50gf$   $250gf \pm 50gf$   
 LIFE TEST: 100,000 cycles

6				
5	HOUSING	PA66	1	BLACK
4	CONTACT	PBS	1	
3	COVER	SPCC	1	Ni-PLATED
2	TERMINAL	BRASS	4	Ag-PLATED
1	KNOB	PA66	1	BLACK/BOWN
NO.	DESCRIPTION	MATERIAL	QTY.	PLATED

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 DATE 制表日 2015/4/13	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE 容許公差 0 ± 0.25 ANG ± SIZE 板線尺寸 A 4 REV 版本 A	PART NAME 品名 12mm X 12mm TACT SWITCH SMT TYPE PITCH: 15mm KONT HEIGHT : 7.3mm OPERATING FORCE: 180g OR 250g REEL PACKING ROHS PART NO. 料號 C8702-FD(B,C)XR000R