


ITEM	DESC	Q'TY	METERIALS	TREATMENT	REMARK
1	STEM	1	HIGH - TEMP THERMOPLASTIC NYLON UL94V - 0	MOLDED BLACK	—
2	FRAME	1	HIGH - TEMP THERMOPLASTIC NYLON UL94V - 0	MOLDED BLACK	—
3	SEALED	1	KAPTON	NONE	—
4	CONTACT	2	STAINLESS STEEL	WITH SILVER PLATING	—
5	SPACER	1	KAPTON	NONE	—
6	BASE	1	NPG-R	WITH TIN /GOLD PLATING	—
7	COVER	1	BRASS	WITH TIN PLATING	—

**NOTE:**

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. GENERAL TOLERANCES MAX.±0.30mm.



CIRCUIT DIAGRAM

P.C.B LAYOUT (SCALE=2:1)

RoHS Compliant

**HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准  
 DWG. 製圖  
 DATE 制表日  
 2020/07/24

SCALE 比例  
 UNIT 單位  
 PAGE 張數  
 M M  
 1 OF 1

TOLERANCE 容許公差  
 .0 ±  
 .00 ±  
 ANG. ±  
 SIZE. 紙張尺寸  
 A 4  
 REV. 版次  
 A

PART NAME 品名  
 1.7X4.5mm TACT SWITCH SIDE PUSH TYPE  
 SEALED TYPE KONB HEIGHT:2.05mm  
 OPERATING FORCE:160gf  
 BUTTON COLOR:BLACK COLOR REEL PACKING ROHS  
 PART NO.  
 料號 C8733-B1BR0000R