



6	COVER (盖板)	1	SUS304	—
5	STEM (按钮)	1	LCP	BLACK
4	TAPE (防尘胶)	1	PI	—
3	CONTACT FORM (弹片)	1	SUS301	Silver coated
2	HOUSING (基座)	1	LCP	BLACK
1	TERMINAL (端子)	1	PHOSPHOR BRONZE (C5191Y)	Ag plating
NO (序号)	PART NAME (部件名)	QTY (数量)	MATERIAL (材料)	REMARK (备注)

SPECIFICATION

1. Rating: DC 12V 50mA Max
2. Contact resistance: 100mΩ MAX
3. Insulation resistance: 100MΩ Min
4. Dielectric strength: 250VAC/min
5. Operating force: 80gf±30gf
6. Operating life: 100,000 cycles

APPD. 核准	SCALE 比例	UNSPECIFIED TOLERANCE 未指定的公差	PART NAME 品名
			3.0mm X 3.9mm TACT SWITCH SMT TYPE KONB HEIGHT: 2.0mm OPERATING FORCE: 80gf WITHOUT LOCATING PEG REEL PACKING BUTTON COLOR: BLACK COLOR ROHS
DWG. 製圖	Betty	ANGULAR (角度)	PART NO.
DATE 制表日	2020/10/05	16 < L ≤ 63 ±0.4	C8739-BINBR000R
		4 < L ≤ 16 ±0.3	料號
		L ≤ 4 ±0.2	
		SIZE. 紙張尺寸	
		A4	
		REV. 版次	
		A	

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.