


材質表 Material List

No.	品名 Part Name	數量 Q'TY	材質 Generic Class
1	端子 Terminal	3	C2680
2	下蓋 Lower Housing	1	PBT Black Color
3	彈簧 Spring	1	SUS304
4	按鈕 Button	1	PBT Black Color
5	接點 Contact	3	銀合金 Silver Alloy
6	切換片 Change Plate	1	C5210
7	壓柄 Lever	1	SUS301
8	上蓋 Upper Housing	1	PBT Black Color



General specifications

回路	Circuit	: ON-ON(1P2T)
額定功率	Rated Voltage	: 125/250V AC 5A
接觸電阻	Contact Resistance	: $\leq 50m\Omega$ (初始值 Initial Value)
絕緣電阻	Insulation Resistance	: $\geq D.C. 500V 100M\Omega$ (初始值 Initial Value)
耐壓強度	Withstand Voltage	: A.C. 1,000V 1minute (初始值 Initial Value)
機械壽命	Mechanical Life	: 100,000 CYCLES
電氣壽命	Electrical Life	: 10,000 CYCLES
耐焊接熱	Soldering Techincs	: 手工焊
適用溫度	Operating Temperature	: -25°C ~ +85°C
適用濕度	Ambient Humidity Used	: < 85%RH
操作力	Operating Force	: 45 ± 20gf
自由位置 (FP)	Free Position	: 19.8 ± 0.8mm
動作位置 (OP)	Operating Position	: 17.8 ± 1.2mm

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	SCALE 比例 參考	DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE UP TO 10 ±0.3 ABOVE 10 TO 100 ±0.5 ABOVE 100 ±0.8 ANGULAR DIMENSIONS ±5°	PART NAME 品名
DWG. 製圖 Betty	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	8.8+7.3mm MICRO SWITCH WITH PLASTICS ROLLER
DATE 制表日 201706/05	PAGE 張數 1 OF 1	REV. 版次 A	5A 125/250VAC CIRCUIT TYPE:1P2T
			LEVER TYPE:14.5mm TERMINAL TYPE:0.6x3.2mm (SOLDER PIN) ROHS
			PART NO. 料號 C8801-05AAA000R