



NO.	Part Name 品名	Q'TY 数量	Generic Class 材质
1	Base 底座	1	Nylon
2	Case 上盖	1	Nylon
3	Button 按钮	1	Nylon
4	Lever 压柄	1	Nylon
5	Spring Plate 弹片	1	C1720
6	Contact 接点	1	Silver alloy
7	Terminal 端子	3	C2680

1. Functional specification			
1.1 Rated Voltage	DC6V	1.5 Free Position (FP)	9.65±0.5mm
1.2 Rated Current	300mA	1.6 Operating Position (OP)	8.65±0.5mm
1.3 Contact resistance	≤100mΩ (Initial value)		
1.4 Operating Force (OF)	10-45gf		
2. Reliability parameter			
2.1 Mechanical life	100,000 CYCLES	2.5 Welding process	Hand soldering - Wave soldering
2.2 Electrical life	50,000 CYCLES	2.6 Operating temperature	-25°C ~ +85°C
2.3 Insulation resistance	≥100MΩ DC250V (Initial value)	2.7 Storage temperature	< 70%RH
2.4 Withstand voltage strength	AC250V 1 minute (Initial value)		

RoHS Compliant **HSM 玄茂科技股份有限公司**
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	SCALE 比例	TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	UNIT 單位	SIZE. 紙張尺寸	2.5MM MICRO SWITCH 3PIN REVERSE RIGHT ANGLE TYPE 0.3A D.C.6V CIRCUIT TYPE:1P2T OPERATING POSITION:8.65MM OPERATING FORCE:10-45gf DIP LENGTH=3.1MM ROHS
DATE 制表日	PAGE 張數	REV. 版次	PART NO. 料號
2021/03/29	1 OF 1	A	C8804-ACBBA000R

