



Notes:

1. Material:
 - 1.1 Insulator: PA66 UL94V-0, Black Color.
 - 1.2 Contact: H62
2. Surface process:
 - 2.1 Terminal: Nickel Plating, 30u" Min.
3. Specification:
 - 3.1 Contact resistance: $\leq 500\text{m}\Omega$
 - 3.2 Insulation resistance: $\geq 1000\text{M}\Omega$
 - 3.3 Voltage resistance: 500 Vr.m.s, 1mA, 60s.
 - 3.4 Insertion force: $\leq 45\text{N}(4.5\text{kgf})$
 - 3.5 Durability (Life Test) : ≥ 3000 Cycles
 - 3.6 Soldering heat resistance temperature: $250^{\circ}\text{C}\pm 5^{\circ}\text{C}$, 10s.
4. Packing: 100pcs/Bag

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	Betty	SCALE 比例 參考	POWER SOCKET CONNECTOR SOLDER TYPE
DATE 制表日	2021/12/22	UNIT 單位 M M	2+6PIN FEMALE NICKEL PLATING
		PAGE 張數 1 OF 1	MATERIAL: PA66 UL94V-0
			BLACK COLOR BAG PACKING ROHS
			PART NO. 料號
			C8981-08FNAB00R