



Specifications:
 Current Rating:1.0 Amp
 Contact resistance:30m Ohm Max.
 Insulator resistance:3000M ohm min. at 500V DC
 Withstanding Voltage:500V AC/Minute
 Operating Temperature Range:-40°~+105°C
 Wire Size Flat Cable I.D.C: 1.0mm Pitch
 Material And Finish
 Insulator:PBT&Glass-fiber reinforced UL94V-0
 Insulator Color:Black
 Contact:Phosphor Bronze
 Contact Plating:See Contact Plating Tab.
 Note:(*)Marked is Important DIM For QC.

No. of Positions

No.	A	B	No.	A	B	No.	A	B
6	11.20	4.00	20	25.20	18.00	40	45.20	38.00
8	13.20	6.00	22	27.20	20.00	44	49.20	42.00
10	15.20	8.00	24	29.20	22.00	50	55.20	48.00
12	17.20	10.00	26	31.20	24.00	60	65.20	58.00
14	19.20	12.00	30	35.20	28.00	68	73.20	66.00
16	21.20	14.00	34	39.20	32.00			

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Hedy		GENERAL $x \pm 0.35$ $xx \pm 0.25$ $xxx \pm 0.10$	ANGLE $x' \pm 5.0'$ $xx' \pm 3.0'$ $xxx' \pm 2.0'$
DWG. 製圖 Yumi	SCALE 比例 參考	UNIT 單位 M M	SIZE. 紙張尺寸 A 4
DATE 制表日 2011/11/07	PAGE 張數 1 OF 1	REV. 版次 A	PART NAME 品名 DIP PLUG 2.0mm X 2.0mm XXP SELECTIVE GOLD BLACK COLOR LOW LEAD PART NO. 料號 C9100-XXSB0000R