



**SPECIFICATIONS**

**Material**

Insulator : PBT glass reinforced, rated UL 94V-0

Contact : Phosphor Bronze or Brass

**Electrical**

Current Rating : 1Amp

Voltage Rating : 250V AC

Contact Resistance : 30 m ohms max.

Insulation Resistance : 3000 M ohms min.

Dielectric Withstanding Voltage : 500V AC for 1 minute

Operating Temperature : -40° ~ +105°

► Flat ribbon cable with 1.0mm pitch.

POSITION	A	B	C
6P	11.34	4.00	2.0
8P	13.34	6.00	2.0
10P	15.34	8.00	2.0
12P	17.34	10.00	2.0
14P	19.34	12.00	2.0
16P	21.34	14.00	2.0
18P	23.34	16.00	2.0
20P	25.34	18.00	2.0
22P	27.34	20.00	2.0
24P	29.34	22.00	2.0
26P	31.34	24.00	2.0
28P	33.34	26.00	2.0
30P	35.34	28.00	2.0
34P	39.34	32.00	2.0
36P	41.34	34.00	2.0
38P	43.34	36.00	2.0
40P	45.34	38.00	2.0
44P	49.34	42.00	2.0
48P	53.34	46.00	2.0
50P	55.34	48.00	2.0
60P	65.34	58.00	2.0
64P	69.34	62.00	2.0

RoHS  
Compliant

**HSM** 玄茂科技股份有限公司  
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 A-mei  
DWG. 製圖 Yumi  
DATE 制表日 2007/10/03

SCALE 比例 參考  
UNIT 單位 MM  
PAGE 張數 1 OF 1

TOLERANCE 容許公差  
.0 ±  
.00 ±  
ANG. ±

SIZE. 紙張尺寸 A4  
REV. 版次 A

PART NAME 品名  
9200-4PNNS1-1 IDC SOCKET 2.0mm X 2.0mm  
XXP WITHOUT BUMP .BLACK ROHS LOW-LEAD

PART NO. 料號 C9200-XXXNXB00R