


Specifications:
 Current Rating:1.0 Amp
 Voltage Rating:250V AC
 Contact resistance:30m Ohm Max. at 6V DC 0.3A
 Insulator resistance:1000M ohm min. at 500V DC
 Withstanding Voltage:500V AC/Minute
 Operating Temperature Range:-40~+105°C
 Wire Size Flat Cable I.D.C: 1.00mm Pitch
 AWG#28(standard) OR #30(Solid)
 Material And Finish
 Insulator:PBT&Glass-fiber reinforced UL94V-0
 Insulator Color:Black
 Contact:Phosphor Bronze
 Contact Plating:See Contact Plating Tab.
 Note:(*)Marked is Important DIM For QC.



| | | | | | | | | | |
|---|------|----|---|---|---|---|---|---|----|
| C | 9200 | 10 | Y | Y | S | B | 0 | 0 | R |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |

- | | | | |
|---|---|-------------------------------|---|
| 1. PRODUCTS: C:Connector 2.SERIES NO.: 9200 3.CONTACT NO.: 04-80 4.FUNCTION: Y:W/ Strain Relief N:W/O Strain Relief | 5.BODY OPTION: Y:W/ Bump N:W/O Bump 6.CONTACT PLATING: S>Selective Gold G:Gold Flash | 7.INSULATOR COLOR: B:Black | 8.FILL IT WITH* 9.FILL IT WITH* 10.R:ROHS |
|---|---|-------------------------------|---|

No. of Positions:

| No. | A | B | C | D | No. | A | B | C | D | No. | A | B | C | D |
|-----|-------|-------|-------|-------|-----|-------|-------|-------|-------|-----|-------|-------|-------|-------|
| 06 | 11.34 | 4.00 | 5.00 | 11.14 | 20 | 25.34 | 18.00 | 19.00 | 25.14 | 38 | 41.34 | 34.00 | 35.00 | 41.14 |
| 08 | 13.34 | 6.00 | 7.00 | 13.14 | 22 | 27.34 | 20.00 | 21.00 | 27.14 | 40 | 45.34 | 38.00 | 39.00 | 45.14 |
| 10 | 15.34 | 8.00 | 9.00 | 15.14 | 24 | 29.34 | 22.00 | 23.00 | 29.14 | 44 | 49.34 | 42.00 | 43.00 | 49.14 |
| 12 | 17.34 | 10.00 | 11.00 | 17.14 | 26 | 31.34 | 24.00 | 25.00 | 31.14 | 50 | 55.34 | 48.00 | 49.00 | 55.34 |
| 14 | 19.34 | 12.00 | 13.00 | 19.14 | 28 | 33.34 | 26.00 | 27.00 | 33.14 | 60 | 65.34 | 58.00 | 59.00 | 65.14 |
| 16 | 21.34 | 14.00 | 15.00 | 21.14 | 30 | 35.34 | 28.00 | 29.00 | 35.14 | 64 | 69.34 | 62.00 | 63.00 | 69.14 |
| 18 | 23.34 | 16.00 | 17.00 | 23.14 | 34 | 39.34 | 32.00 | 33.00 | 39.14 | | | | | |

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

| | | | |
|------------------------------------|---|--|-------------------|
| APPD. 核准 HELEN | TOLERANCE 容許公差 X ± 0.35 X' ± 5.0' XX ± 0.25 XX' ± 3.0' XXX ± 0.10 XXX' ± 2.0' | PART NAME 品名 IDC SOCKET 2.0mm X 2.0mm XXP WITH BUMP BLACK INSULATOR ROHS | |
| DWG. 製圖 ABBY | | | UNIT 單位 M M |
| DATE 制表日 2012/07/05 | | | PAGE 張數 1 OF 1 |
| PART NO. 料號 C9200-XXXXYXB00R | | | |