


NUT



1. MATERIAL :
 - 1-1. HOUSING : PBT UL94V-0 ; COLOR : BLACK
 - 1-2. CONTACT : BRASS
 - 1-3. NUT : BRASS
 - 1-4. SHELL : BRASS
 - 1-5. O-RING : EPDM
2. FINISH :
 - 2-1. CONTACT : 10 MICRO INCHES MIN. GOLD PLATED
UNDER PLATE : NICKEL
 - 2-2. NUT : NICKEL PLATED
 - 2-3. SHELL : NICKEL PLATED
3. ELECTRICAL SPECIFICATION :
 - 3-1. Rated current : 4A
 - 3-2. Rated Voltage : 250V
 - 3-3. Water proof : IPX7
 - 3-4. INSULATION RESISTANCE : 1000MΩ MIN
 - 3-5. DIELECTRIC WITHSTANDING VOLTAGE : 800V
 - 3-6. CONTACT RESISTANCE : < 10mΩ
4. Environmental :
 - 4-1. Operation Temperature : -40℃~85℃

RECOMMEND PANEL CUT-OUT RECOMMEND P.C.B LAYOUT

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	TOLERANCE × ±0.20 ×× ±0.10 ××× ±0.05 ×××× ±0.03 ANGULA ±1°	PART NAME 品名 M12*1.0 4PIN MALE PANEL MOUNT IP67 WATERPROOF TYPE B-Code DIP 180° TYPE GOLD 10U" PLATING BLACK COLOR ROHS
DWG. 製圖 Betty	UNIT 單位 M M	SIZE 紙張尺寸 A 4	PART NO.
DATE 制表日 2020/03/11	PAGE 張數 1 OF 1	REV. 版次 A	料號 C9302-04MABB00R