



1. MATERIAL :
 - 1-1. HOUSING : PBT ; COLOR : BLACK
 - 1-2. CONTACT : BRASS.
 - 1-3. SHELL : BRASS
 - 1-4. O-RING : NBR ; COLOR : BLACK
 - 1-5. NUT : BRASS.
2. FINISH :
 - 2-1. CONTACT : SEE TABLE A
 - 2-2. SHELL : NICKEL PLATED.
 - 2-3. NUT : NICKEL PLATED.
3. ELECTRICAL SPECIFICATION :
 - 3-1. Rated current : 2A
 - 3-2. Rated voltage : 30V
 - 3-3. Water proof : IP67
 - 3-4. INSULATION RESISTANCE : 1000MΩ MIN
 - 3-5. DIELECTRIC WITHSTANDING VOLTAGE : 800V
 - 3-6. CONTACT RESISTANCE : < 10mΩ
4. Environmental :
 - 4-1. Operation Temperature : -40℃~105℃

TABLE A

5P	6P
C9323-06MABB00R	10u" GOLD PLATED / 鍍金10u"
C9323-05MAGB00R	GOLD FLASH PLATED / 鍍表金
C9323-05MABB00R	10u" GOLD PLATED / 鍍金10u"
PART No.	FINISH

RoHS Compliant	玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
	APPD. 核准 DWG. 製圖 DATE 制表日 2020/04/20	SCALE 比例 UNIT 單位 PAGE 張數 1 OF 1
Betty	TOLERANCE .x ±0.20 .xx ±0.10 .xxx ±0.05 .xxxx ±0.03 ANGULA ±1°	PART NAME 品名 M8 XXPIN MALE 180° SOLDER TYPE IP67 WATERPROOF TYPE FRONT LOCK M8*1.0mm BLACK COLOR ROHS
	SIZE 紙張尺寸 A 4	PART NO. 料號 C9323-XXMAXB00R

NUT

RECOMMENDPANEL CUT-OUT