



T:1.6 Dimensions of PC board holes
 Tolerance : ±0.05(Printed-top view)

LEAD FREE

10	NUT	1	H59(COPPER ALLOY)	Ni PLATED
9	TERMINAL	1	C5191 t=0.4	Ag PLATED
8	TERMINAL	1	C5191 t=0.3	Ag PLATED
7	RING SPRING	1	C5191 t=0.35	Ag PLATED
6	EARTH TERMINAL	1	C2680 t=0.4	Ag PLATED
5	BREAK TERMINAL	1	C5191 t=0.35	Ag PLATED
4	TIP SPRING	1	C2680 t=0.4	Ag PLATED
3	EARTH TERMINAL	1	C5191 t=0.3	Ag PLATED
2	COVER	1	ABS	UL-94HB(BLACK)
1	HOUSING	1	ABS	UL-94HB(BLACK)

Specification:
 Rated Voltage / Rated Current: D.C. 12V 1A
 Operating Temp: -40°C~+70°C
 Insulation Resistance:100MΩ min
 Dielectric Withstanding Voltage: 500V A.C For 1min
 Contact Resistance:30mΩ max
 UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

LTR	PART NAME	QTY	MATERIAL	REMARK
RoHS Compliant				
HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.				
APPD. 核准	SCALE 比例	TOLERANCE 容許公差	PART NAME 品名	
DWG. 製圖	UNIT 單位	SIZE 線規尺寸	6.4Φ PHONE JACK 7P W/ PLASTIC INSULATOR W/ 4 POSTS SILVER PLATING BLACK INSULATOR ROHS	
DATE 制表日	PAGE 張數	REV. 版本	PART NO. 料號	
2020/9/4	1 OF 1	B	C9602-07PCVB00R	