



Operating Temperature: -30~70°C  
 Rated Loaded: DC30V 0.5A  
 Contact Resistance:  $\leq 0.03\Omega$   
 Insulation Resistance:  $\geq 100m\Omega$  DC250V  
 Withstand Voltage: AC500V(50Hz), 1min.  
 Withdraw force: 3~25N  
 Life Test: 5,000 cycles

5	3# Reed	1	QSn6.5-0.1 Tin bronze $\delta = 0.25mm$	D L1Ag
4	1# Reed	1	QSn6.5-0.1 Tin bronze $\delta = 0.25mm$	D L1Ag
3	1# Reed	1	QSn6.5-0.1 Tin bronze $\delta = 0.25mm$	D L1Ag
2	1# Reed	1	QSn6.5-0.1 Tin bronze $\delta = 0.25mm$	D L1Ag
1	MATERIAL	1	PPA	
NO.	DESCRIPTION	QTY.	PLATING	

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 Hedy DATE 制表日 2018/03/01	SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 / 1	TOLERANCE 容許公差 .0 ± .00 ± ANG. ± SIZE. 紙張尺寸 A 4 REV. 版次 A	PART NAME 品名 3.5Φ EARPHONE JACK 6PIN SMT TYPE W/ TWO PLASTIC POSTS SILVER PLATING BLACK INSULATOR BAG PACKING ROHS PART NO. 料號 C9611-06AVBB00R