



T:1.6 Dimensions of PC board holes
Tolerance : ±0.1(Printed-top view)

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

CAT. NO.	PIN	SCHEMATIC
C9731-CCNB0000R	φ2.0	
C9731-DCNB0000R	φ2.5	
C9731-HCNB0000R	φ2.35	

LEAD FREE

LTR	PART NAME	QTY	MATERIAL	REMARK
6	HOUSING	1	PBT 4815	UL-94V0
5	COVER	1	PF	
4	PIN	1	C2680	MB:Cu Ni PLATED
3	SHUNT TERMINAL	1	C2680 t=0.3	MB:Cu Sn PLATED
2	TIP SPRING	1	C5191 t=0.3	MB:Cu Sn PLATED
1	CENTER PIN TERMINAL	1	C2680 t=0.3	MB:Cu Sn PLATED

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准		TOLERANCE 容許公差 .0 ± 0.3 .00 ± ANG. ±	PART NAME 品名 DC POWER JACK STRAIGHT TYPE NORMAL CLOSE CONTACT PLATING: NICKEL BLACK INSULATOR ROHS
DWG. 製圖 Helen	SCALE 比例 參考	SIZE 紙張尺寸 A4	PART NO. 料號 C9731-XCNB0000R
DATE 制表日 2013/1/20	UNIT 單位 MM	PAGE 張數 1 OF 1	REV. 版本 A