



SPECIFICATIONS:

Contact Resistance : 30mΩ max
 Current Rating : Max 5.0A, 24VDC
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstand Voltage AC 500V for one minute
 Remark: ▲ : The Most Important Dimension

NO.	Description	Material	Q'TY	Finish
6.	Ring	0.3T SUS 304	1	
5.	Earth Terminal(Barrel)	0.15T SUS 304	1	
4.	Housing	PBT+30%	1	Black Color
3.	Pin(φ2.5)	Brass	1	Gold Plated
2.	Terminal	0.25T Phosphor Bronze	1	Silver Plated
1.	Shell	0.2T Steel	1	Nickel Plated

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准
 DWG. 製圖
 DATE 制表日
 2015/02/09

SCALE 比例 參考
 UNIT 單位 M M
 PAGE 張數 1 OF 1

TOLERANCE 容許公差
 .0 ± 0.30
 .00 ± 0.20
 ANG. ± 3°
 SIZE. 紙張尺寸 A 4
 REV. 版次 A

PART NAME 品名
 DC POWER JACK φ2.5mm
 GOLD PLATING BLACK INSULATOR
 ROHS

PART NO.
 料號 C9740-DGB00000R