



6	HOUSING	1	PA9T	UL-94V0(BLACK)
5	PIN	1	H59(COPPER ALLOY)	Sn PLATED
4	TERMINAL	1	C2680	t=0.25 Ag PLATED
3	CURVE PIECE	1	C2680	t=0.25 Ag PLATED
2	SPRING FOOT	1	SUS301	t=0.30 Ag PLATED
1	CONTACT FOOT	1	C2680	t=0.25 Ag PLATED

RoHS Compliant	玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.									
APPD. 核准 DWG. 製圖 Betty DATE 制表日 2015/12/21	<table border="1"> <tr> <td> SCALE 比例 參考 </td> <td> TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3° </td> <td> PART NAME 品名 DC POWER JACK SMT TYPE φ1.3mm NORMAL CLOSE TIN PLATING W/ LOCATING PEG BLACK INSULATOR INSULATOR MATERIAL:PA9T REEL PACKING ROHS </td> </tr> <tr> <td> UNIT 單位 M M </td> <td> SIZE. 紙張尺寸 A 4 </td> <td> PART NO. 料號 C9741-ACTBR000B </td> </tr> <tr> <td> PAGE 張數 1 OF 2 </td> <td> REV. 版次 A </td> <td></td> </tr> </table>	 SCALE 比例 參考	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 DC POWER JACK SMT TYPE φ1.3mm NORMAL CLOSE TIN PLATING W/ LOCATING PEG BLACK INSULATOR INSULATOR MATERIAL:PA9T REEL PACKING ROHS	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 C9741-ACTBR000B	PAGE 張數 1 OF 2	REV. 版次 A	
 SCALE 比例 參考	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 DC POWER JACK SMT TYPE φ1.3mm NORMAL CLOSE TIN PLATING W/ LOCATING PEG BLACK INSULATOR INSULATOR MATERIAL:PA9T REEL PACKING ROHS								
UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 C9741-ACTBR000B								
PAGE 張數 1 OF 2	REV. 版次 A									