



SPECIFICATION
 PITCH BETWEEN POLES :1.25mm
 CURRENT RATING : 1A
 VOLTAGE RATING : 100V
 CONTACT RESISTANCE : INITIAL VALUE/10mΩ max.
 AFTER ENVIRONMENTAL TESTING/20mΩ max.
 INSULATION RESISTANCE : 100MΩ(min.)
 WITHSTAND VOLTAGE : 500V AC/MINUTE
 TEMPERATURE RANGE : -25°C TO +85°C
FEATURES:
 AVAILABLE NUMBER OF CIRCUITS 2 TO 20
 MATERIAL : P.B.T UL94V-0

Dimensional and Order information

Poles	DIM:(mm)	
	A	B
2	1.25	4.25
3	2.50	5.50
4	3.75	6.75
5	5.00	8.00
6	6.25	9.25
7	7.50	10.50
8	8.75	11.75
9	10.00	13.00
10	11.25	14.25

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE: .000 ±0.08 .00 ±0.13 .0 ±0.25	PART NAME 品名 1.25mm HOUSING 1XXXP WHITE COLOR MATERIAL:PBT UL94-0 ROHS
DWG. 製圖 Betty		SIZE: 紙張尺寸 A 4	PART NO. 料號 H1027-XXPPW0000R
DATE 制表日 2013/01/18		REV. 版次 A	