



NOTE:  
 \* Material: PBT UL94V-0 Black  
 \* Current rating: 1A AC,DC  
 \* Voltage rating: 100V AC,DC  
 \* Temperature range: -25°C ~ +85°C

CKTS	DIM. "A"	DIM. "B"	CKTS	DIM. "A"	DIM. "B"
4	0.150(3.81)	0.242(6.15)	15	0.700(17.78)	0.792(20.12)
5	0.200(5.08)	0.292(7.42)	16	0.750(19.05)	0.842(21.39)
6	0.250(6.35)	0.342(8.69)	17	0.800(20.32)	0.892(22.66)
7	0.300(7.62)	0.392(9.96)	20	0.950(24.13)	1.042(26.47)
8	0.350(8.89)	0.442(11.23)	22	1.050(26.67)	1.142(29.01)
10	0.450(11.43)	0.542(13.77)	25	1.200(30.48)	1.292(32.82)
11	0.500(12.70)	0.592(15.04)	26	1.250(31.75)	1.342(34.09)
12	0.550(13.97)	0.642(16.31)	30	1.450(36.83)	1.542(39.17)
13	0.600(15.24)	0.692(17.58)			

RoHS  
Compliant

**HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准	 SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3° SIZE 紙張尺寸 A 4 REV. 版次 B	PART NAME 品名 1.27mm FFC/FPC HOUSING SINGLE ROW 1XXXP WITHOUT LOCKING RIBS PBT UL94-V0 BLACK INSULATOR ROHS
DWG. 製圖 Betty		PART NO. 料號 H1271-XXPNBP00R	
DATE 制表日 2020/10/07			