


MATERIAL: NYLON66, UL94V-0
 PC BOARD THICKNESS: 1.2mm, 1.6mm
 VOLTAGE RATING: AC, DC, 250V
 CURRENT RATING: AC, DC, 2A
 TEMPERATURE RANGE: -25°C TO +85°C
 HOLE DIAMETER: $\phi 0.8 \begin{matrix} +0.1 \\ -0.05 \end{matrix}$
 INSULATION RESISTANCE: 1.000M Ω MIN.
 WITHSTAND VOLTAGE: 800V AC/MINUTE

DIMENSION: (MM)
 P: 2.0 ± 0.1
 W: 3.3 ± 0.3
 H: 6.0 ± 0.25

	A ± 0.3	B ± 0.2
2	5.2	2.0
3	7.2	4.0
4	9.2	6.0
5	11.2	8.0
6	13.2	10.0
7	15.2	12.0
8	17.2	14.0
9	19.2	16.0
10	21.2	18.0
11	23.2	20.0
12	25.2	22.0
13	27.2	24.0
14	29.2	26.0
15	31.2	28.0
16	33.2	30.0
17	35.2	32.0
18	37.2	34.0
19	39.2	36.0
20	41.2	38.0

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差	PART NAME 品名 2.0mm HOUSING 1XXXP WHITE COLOR ROHS
DWG. 製圖 Hedy	SCALE 比例 參考	.0 \pm .00 \pm ANG. \pm	PART NO. 料號 H2006-XXPW0000R
DATE 制表日 2014/08/08	UNIT 單位 MM	SIZE. 紙張尺寸 A 4	
	PAGE 張數 1 / 1	REV. 版次 A	