



Features:

- Material: UL 94V-0 nylon 66
- Positive housing lock & Fully isolated terminal
- Low engagement force terminal
- Color: Black

Specification:

- Current rating and wire size:

△1 △2	Wire type (AWG)	UL 1007	
		#22	#24
	Current rating	4 A	3 A

- Voltage rating: 600V (R.M.S.)
- Insulation resistance: DC 500V 1000MΩ Min.
- Dielectric withstanding voltage: 1500V AC/minute
- Ambient temperature range: -40°C ~ 105°C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例	UNLESS OTHERWISE SPECIFIED TOLERANCE .000 ± 0.08 (mm) .00 ± 0.25 (mm) .0 ± 0.4 (mm)	PART NAME 品名 4.2MM MALE HOUSING 2X3PIN OUTLET HOLE: LEFT MATERIAL: NYLON66 UL94V-0 BLACK COLOR ROHS
DWG. 製圖	UNIT 單位	SIZE. 紙張尺寸	PART NO.
DATE 制表日 2022/01/03	Betty	M M	H5152-06PDLB10R
	PAGE 張數	REV. 版次	料號
	1 OF 1	A	