



Features:

- Material: UL 94V-0 nylon 66
- Positive housing lock & Fully isolated terminal
- Low engagement force terminal
- Color: Black

Specification:

- Current rating and wire size:

△1 △2	Wire type (AWG)	UL 1007	
		#22	#24
	Current rating	4 A	3 A

- Voltage rating: 600V (R.M.S.)
- Insulation resistance: DC 500V 1000MΩ Min.
- Dielectric withstanding voltage: 1500V AC/minute
- Ambient temperature range: -40°C ~ 105°C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		UNLESS OTHERWISE SPECIFIED TOLERANCE .000 ± 0.08 (mm) .00 ± 0.25 (mm) .0 ± 0.4 (mm)	PART NAME 品名 4.2MM MALE HOUSING 2X3PIN OUTLET HOLE:RIGHT ANGLE MATERIAL:NYLON66 UL94V-0 BLACK COLOR ROHS
DWG. 製圖	Betty	SCALE 比例 參考	PART NO. 料號 H5152-06PDRB10R
DATE 制表日	2022/01/03	UNIT 單位 M M	
		PAGE 張數 1 OF 1	
		SIZE. 紙張尺寸 A 4	
		REV. 版次 A	