



SPECIFICATIONS :
 Voltage Rating: 50V AC / DC
 Current Rating: 1A AC / DC
 Withstanding Voltage: 500V AC/minute
 Temperature Range: -25°C~+85°C
 Insulation Resistance: 100MΩ Min.
 Contact Resistance: 20mΩ Max.
 Material: Nylon66, UL94V-0
 Color: Natural

Poles	Dimensions(mm)		
	A	B	C
02	1.00	3.00	2.40
03	2.00	4.00	3.40
04	3.00	5.00	4.40
05	4.00	6.00	5.40
06	5.00	7.00	6.40
07	6.00	8.00	7.40
08	7.00	9.00	8.40
09	8.00	10.00	9.40
10	9.00	11.00	10.40
11	10.00	12.00	11.40
12	11.00	13.00	12.40
13	12.00	14.00	13.40
14	13.00	15.00	14.40
15	14.00	16.00	15.40
16	15.00	17.00	16.40

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
	APPD. 核准 Betty DWG. 製圖 Lena DATE 制表日 2023/5/16	TOLERANCE 容許公差 0 ± 0.30 .00 ± 0.20 .000 ± 0.10 UNIT 單位 M M PAGE 張數 1 OF 1