



■ **TERMINAL**

- **Material : Phosphor bronze**
- **Thickness : 0.15mm**
- **Plating : Gold plated**
- **Wire Range : Suitable for AWG#30~36**
- **Insulation O.D : 0.75mm (max)**
- **Q'TY : 15,000pcs/reel**

■ **SPECIFICATIONS**

- **Voltage rating: 200V AC, DC**
- **Current rating: 0.8A**
- **Withstand Voltage : 500V AC/ minute**
- **Insulation resistance: 100MΩ min**
- **Contact resistance: 50mΩ max**
- **Temperature range: -40~+80°C**

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCES UNLESS NOTED		PART NAME 品名 0.5mm LVDS TERMINAL MATERIAL : PHOSPHOR BRONZE GOLD FLASH PLATING SUITABLE FOR 30~36AWG ROHS
DWG. 製圖 ABBY		LINEAR ±	.x ±0.3 .xx ±0.15 .xxx±0.08	
DATE 制表日 2012/08/07	UNIT 單位 MM	ANGLES ±	2°	PART NO. 料號 T1005-GPOA0000R
	PAGE 張數 1 OF 1	SIZE. 紙張尺寸 A 4	REV. 版次 B	