



SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 650V AC/minute
 Pin Material: Brass/Gold-flash
 Material: Nylon 6T,UL94V-0
 Color: Natural(Black)

Circuit No.	Dimensions		Circuit No.	Dimensions	
	A	B		A	B
02P	2.00	6.00	09P	16.00	20.00
03P	4.00	8.00	10P	18.00	22.00
04P	6.00	10.00	11P	20.00	24.00
05P	8.00	12.00	12P	22.00	26.00
06P	10.00	14.00	13P	24.00	28.00
07P	12.00	16.00	14P	26.00	30.00
08P	14.00	18.00	15P	28.00	32.00

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 DATE 制表日 2015/12/21	SCALE 比例 UNIT 單位 PAGE 張數 1 OF 1	TOLERANCE 容許公差 0 ±0.25 .00 ±0.15 ANG. ±	PART NAME 品名 2.0mm WAFER RIGHT ANGLE TYPE 1X??P GOLD FLASH PLATING BLACK COLOR (NYLON6T UL94V-0) ROHS PART NO. 料號 W1001-XXPRGB00R
Helen		SIZE 線規尺寸 A 4	REV. 版本 A