



**MATERIAL:**

WAFER:HIGH TEMPERA TURE PLASTIC  
 NYLON46 UL94V-0  
 PIN:HIGH STRENGTH BRASS  
 WITH TIN OVER NICKEL PLATED

**SPECIFICATION:**

Current Rating: 1A AC, DC  
 Voltage Rating: 125V AC,DC  
 Operating Temp.: -40°C ~ +85°C  
 Insulation Resistance: 100MΩ/ min.  
 Dielectric Withstanding Voltage: 250V AC/ minute  
 Contact Resistance: 20mΩ/ max.

CKT.	A	B	C	D
2	1.25	3.05	4.25	7.65
3	2.50	4.30	5.50	8.90
4	3.75	5.55	6.75	10.15
5	5.00	6.80	8.00	11.40
6	6.25	8.05	9.25	12.65
7	7.50	9.30	10.50	13.90
8	8.75	10.56	11.75	15.15
9	10.00	11.80	13.00	16.40
10	11.25	13.05	14.25	17.65
11	12.50	14.30	15.50	18.90
12	13.75	15.55	16.75	20.15
13	15.00	16.80	18.00	21.40
14	16.25	18.05	19.25	22.65
15	17.50	19.30	20.50	23.90

RoHS  
Compliant

**HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD.  
核准 Angel  
 DWG.  
製圖 HELEN  
 DATE 制表日 2012/3/8

SCALE  
比例 參考  
 UNIT  
單位 M M  
 PAGE  
張數 1 OF 1  
 TOLERANCE  
容許公差  
 0 ±0.15  
 .00 ±0.25  
 ANG.  
±  
 SIZE.  
紙張尺寸 A 4  
 REV.  
版次 B

PART NAME 品名  
 1.25mm WAFER XXP SMT TYPE RIGHT  
 ANGLE (SIDE ENTRY) BEIGE COLOR  
 ROHS LOW-LEAD  
 PART NO.  
 料號 W1125-XXPBXXC0R

