



- SPECIFICATIONS**
- Current Rating : 1A AC/DC
  - Withstanding Voltage : 250V AC /minute
  - Insulation Resistance : 100MΩ min
  - Temperature Range : - 40°C to + 85°C
  - Contact Resistance : 20mΩ max

- WAFER**
- Poles : 2-15(DIP Type)
  - Material : 1.Contact : Brass, Tin Plated  
2. Base : Nylon PA46 UL94V-0 ;Color:Nature
  - Finish : Tin Plated
  - Q' ty : 1,000 pcs./PVC Box

Poles	Dimensions (mm)			Poles	Dimensions (mm)		
	A	B	C		A	B	C
2	1.25	4.25	3.05	9	10.00	13.00	11.80
3	2.50	5.50	4.30	10	11.25	14.25	13.05
4	3.75	6.75	5.55	11	12.50	15.50	14.30
5	5.00	8.00	6.80	12	13.75	16.75	15.55
6	6.25	9.25	8.05	13	15.00	18.00	16.80
7	7.50	10.50	9.30	14	16.25	19.25	18.05
8	8.75	11.75	10.55	15	17.50	20.50	19.30

<p>RoHS Compliant</p>		<p><b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准 <b>BETTY</b></p>	<p>DWG. 製圖 <b>BETTY</b></p>	<p>SCALE 比例 參考</p> <p>UNIT 單位 M M</p> <p>PAGE 張數 1 OF 1</p>	<p>TOLERANCE .0 ±0.30 .00 ±0.20 .000 ±0.10</p> <p>ANGLE 0° ±1°</p> <p>SIZE. 紙張尺寸 A 4</p> <p>REV. 版次 B</p>
<p>DATE 制表日 2011/05/18</p>		<p>PART NAME 品名 1.25mm WAFER DIP RIGHT ANGLE TYPE 1XXXP TIN PLATED IVORY COLOR ROHS</p> <p>PART NO. 料號 W1359-XXPRT010R</p>	