



- SPECIFICATIONS**
- Voltage Rating : 250V AC/DC
 - Current Rating : 1A AC/DC
 - Withstanding Voltage : 250V AC /minute
 - Insulation Resistance : 100M Ω min
 - Temperature Range : - 40°C to + 85°C
 - Contact Resistance : 20m Ω max

- WAFER**
- Code No. Poles : 2 - 15(DIP Type)
- Material : Contact : Brass, Tin Plated
Base : Nylon 66 UL94V-0
 - Package : PVC Box

Poles	Dimensions (mm)		
	A	B	C
2	1.25	4.25	3.05
3	2.50	5.50	4.30
4	3.75	6.75	5.55
5	5.00	8.00	6.80
6	6.25	9.25	8.05
7	7.50	10.50	9.30
8	8.75	11.75	10.55
9	10.00	13.00	11.80
10	11.25	14.25	13.05
11	12.50	15.50	14.30
12	13.75	16.75	15.55
13	15.00	18.00	16.80
14	16.25	19.25	18.05
15	17.50	20.50	19.30

RoHS Compliant		HSM 玄茂科技股份有限公司		HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE .0 ±0.30 .00 ±0.20 .000 ±0.10	PART NAME 品名 1.25mm WAFER DIP STRAIGHT TYPE 1XXXP TIN PLATED IVORY COLOR ROHS		
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE. 紙張尺寸 A 4	PART NO. 料號 W1359-XXPST010R		
DATE 制表日 2015/06/09	PAGE 張數 1 OF 1	REV. 版次 A			