



- NOTES:  
**SPECIFICATION**  
 1. Current : 4A max.  
 2. Voltage: 250V AC max.  
 3. Insulation Resistance: 1000 Megohms Min.  
 4. Contact Resistance: 10 Milliohms Max.  
 5. Dielectric Withstanding Voltage: 1000V AC  
 6. Operating Temperature: -40°C to +80°C

NO. OF CONTACT	Dimension		NO. OF CONTACT	Dimension	
	A	B		A	B
02	3.96	8.06	10	35.64	39.74
03	7.92	12.02	11	39.60	43.70
04	11.88	15.98	12	43.56	47.66
05	15.84	19.94	13	47.52	51.62
06	19.80	23.90	14	51.48	55.58
07	23.76	27.86	15	55.44	59.54
08	27.72	31.82	16	59.40	63.50
09	31.68	35.78			

<b>RoHS Compliant</b>	<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>		
	APPD. 核准 Betty DWG. 製圖 Lena DATE 制表日 2022/4/14	TOLERANCE 容許公差 0 ± 0.35 .00 ± 0.10 ANG. ±	PART NAME 品名 3.96mm WAFER 1XXXP BOTTOM ENTRY TYPE WITH LOCKING RIBS WHITE INSULATOR ROHS
	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	SIZE 線規尺寸 A4 REV. 版本 C	PART NO. 料號 W1396-XXPBYXW0R
	圖號: 1396-XXPBYXW0R		