



PA4T UL 94V-0	Phorphos bronze	Gold-Flash	Brass	Nickel
Material	Material(Pin)	Finish(Pin)	Material (Solder Tabs)	Finish (Solder Tabs)

- Specification**
- Rated voltage: 150V AC/DC
  - Rated current: 3A AC/DC
  - Voltage resistance: 500V AC/minute
  - Working temperature: -25°C ~ +85°C
  - Insulation resistance: ≥ 1000MΩ
  - Contact resistance : ≤ 20mΩ

Poles	Dimensions(mm)			
	A	B	C	D
02	1.50	6.75	2.85	
03	3.00	8.25	4.35	
04	4.50	9.75	5.85	
05	6.00	11.25	7.35	3.00
06	7.50	12.75	8.85	3.00
07	9.00	14.25	10.35	3.00
08	10.50	15.75	11.85	3.00
09	12.00	17.25	13.35	6.00
10	13.50	18.75	14.85	8.55
11	15.00	20.25	16.35	10.50
12	16.50	21.75	17.85	12.00

RoHS Compliant **HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准	 SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1	GENERAL TOLERANCE X ±0.30 .XX ±0.20 .XXX ±0.10	PART NAME 品名 1.50mm WAFER 1XXXPIN SMT RIGHT ANGLE TYPE GOLD PLATING BLACK COLOR REEL PACKING ROHS
DWG. 製圖 Betty		SIZE 紙張尺寸 A 4	PART NO. 料號 W1502-XXPBGRB0R
DATE 制表日 2020/03/11		REV. 版次 B	